
TECHNICAL DATA SHEET
(Additive MFQ-STAB-1031)

• **Product Description:**

MFQ-STAB-1031 excellent long-term heat stability
MFQ-STAB-1031 pigmenting effect of basic primary lead Stabilizers beneficial in light coloured applications
MFQ-STAB-1031 low solubility in water, no leaking into the environment
MFQ-STAB-1031 no odor during processing and in the final product
MFQ-STAB-1031 No detrimental effects on the softening temperature of rigid PVC

• **General Properties:**

Forms	•Flake
Color	•Dark

• **Technical Specifications:**

Compounds	organic and inorganic materials
Solubility in water	Indissoluble
Ash	1±23
Moisture Content	max 1 %
Phr	5/2-5/3
Soft Point(°C) orMP	1±100 °C

ATTENTION

- ✓ **Dosage:** 5% to 10% film depending on final application and thickness.
- ✓ **Lifetime and Storage:** Not to exceed 12-18 months. Keep in cool and dry place under shelter for long periods.

* This product packed in PP Woven bag of 25 kg each

Address No.: 811, Eighth Floor, Palmyra Commercial and Administrative Complex, Madani Avenue,
Western Janbazan, Narmak, TEHRAN – IRAN www.marinafq.com

TEL: +98-21-77850569

+98-21-77850591

+98-21-77850536

WhatsApp: +98-9916593655

Email: commercial@marinafq.com

www.marinafq.com